

# MYK AQUAFIN UM

## 2-component cement based flexible Waterproof Coating

### Description:

**MYK AQUAFIN-UM** is an economic cementitious, polymer dispersion based highly flexible protective coating and waterproof barrier. This product is two-component and resistant to water, moisture and abrasion. Its liquid mixing component is solvent free.

**MYK AQUAFIN -UM** is a stand-alone product. It can be top or over-coated with flexible or rigid mortars, stuccos or coatings for uniform appearance. It bridges shrinkage cracks.

**Pack Size: 33.33 Kg Pack**

### Advantages:

- Seamless and joint-less flexible waterproofing.
- Can be applied by brush, trowel or sprayed with suitable device
- Bonds to moist surfaces without prime coat.
- Diffusion opens. Act strongly aggressive towards concrete in accordance with DIN 4030.
- Highly crack-bridging.
- Solvent-free

### Usage:

- Horizontal, Vertical or overhead applications
- Exterior (positive side) or interior (negative side) waterproofing of new or old below grade foundations.
- Balconies, plaza decks, in combination with a UV protection
- Underneath tile mortars (showers, sanitary rooms, kitchens, pools etc.
- Water, wastewater, sea water and marine aquarium tanks and other reinforced concrete structures.

[www.shirazee.co.in](http://www.shirazee.co.in)

### Mixing & Application:

- Take 1/3<sup>rd</sup> content of the liquid **MYK Aquafin UM** & pour into a clean container and add **MYK Aquafin UM** powder into it.
- Stir well with a mechanical means until lump free homogeneous mix is obtained.
- The application of **MYK AQUAFIN-UM** is a simple brush application. Use soft bristle brush.

### Consumption:

1.5 to 2.5 kg subject to application areas.

### Health & Safety

Use of hand gloves is necessary while mixing the product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

**Storage:** Store in cool dry place

**Shelf Life:** 12 months from date of manufacturing.