

MYK Coat ZP

Epoxy Zinc Rich Primer

Description:

MYK Coat ZP is a two component anticorrosion primer for reinforced steel in concrete repairs. It actively resists corrosion within the confines of the repair location.

Pack Size: 1 Kg Pack**Advantages:**

- Zinc rich system combats corrosion
- Permanent protection to the steel structure
- Excellent adhesion to steel
- Time Saving-touch dry after 35 to 40 Minutes
- Exhibits excellent bond strength in cementitious repair

Usage:

- Used as a primer on reinforced bars for anticorrosive system and in concrete repairs
- Also can be used on exterior surfaces as a coating of machinery, fertilizers tanks, and girders in industries.

Mixing & Application:

Stir the Hardener and Resin individually with drill mixer of proper size. Then add the entire content of the hardener into Resin container and stir the two components thoroughly using a low speed mixer for about 2 to 3 Minutes until a uniform color of the mixture is obtained.

Corroded steel shall be fully exposed and all loose scale and corrosion deposits shall be removed. Then apply **MYK Coat ZP** as soon as possible over the dry steel surface after completion of the preparation work by using brush.

Consumption:

6.5 m² per Kg @ 50 microns.

Health & Safety

Use of hand gloves is necessary while mixing the product. In case of contact with skin or eyes, use plenty of water to wash and obtain medical help immediately.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.