

# MYK KRACKFILL

## Crack repair Mortar

### **Description:**

It is a cement based polymer modified powder material for filling cracks in plastered surfaces. It is ideal to fill 2 to 3 mm wider static cracks, it has strong adhesion and also non-shrink in nature. It comes in two colours White & Grey.

### **Pack Size: 1, 5 & 25 Kg Pack**

### **Advantages:**

- Adhesion - Strong adhesion to common building substrates.
- Easy to use
- Good water resistance properties & weathering durability
- Eco- friendly – Does not contain solvent.
- Non shrink in nature

### **Usage:**

- To fill the static cracks of 2 to 3 mm sizes
- To level the undulation of the unplastered or plastered ceilings and walls
- To provide smooth finish to brick and stone,

### **Mixing & Application:**

Remove all loose particles from the surface then moisten the surface before doing the coating application. Then apply MYK Bond SBR 45 by brush application. Mixing ratio of Crack-Fill Powder to water varies with respect to area of application. For surface leveling- the ratio is 2 parts of powder to 1 part of water and mix until we get homogeneous consistency. For filling deep holes and cracks - reduce the water quantity to get a thicker pasty consistency. Start addition of crack filler powder gradually under continuous mixing till a homogeneous lump free mix is obtained after addition of balance quantity of water. For smaller mixes wooden or metal spatula can be used and mixed manually. The total mixing time shall not be more than 5 minutes.

### **Consumption:**

The coverage varies with different application. For crack filling-1 kg powder with 500 ml water will fill a crack of 4 mm width by 4 mm depth upto 40 linear meter.

### **Health & Safety**

Use of hand gloves is necessary while mixing the product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

**Storage:** Store in cool dry place

**Shelf Life:** 12 months from date of manufacturing.