

MYK AQUAFIN 2C

2-Component High Elongation Crack Bridging Waterproof Coating

Description:

MYK AQUAFIN 2C is a state of the art, highly flexible, crack bridging waterproof coating.

Pack Size: 35 Kg Composite Pack**Advantages:**

- Can be easily applied
- Solvent free - environment friendly
- Root resistant coating
- Applied to moist or damp substrates
- Permanently flexible coating, tensile elongation up to 80%
- Crack bridging up to 1.5 mm
- Resists strong hydrostatic pressure (tested up to 140 m water head, positive side), according to Standard DIN 4030.
- Potable water approval according to DVGW W347
- Available in different colors and can be painted or top-coated, providing designer and applicators with limitless possibilities for finished applications

Usage:

Basements, Retaining walls

- Podium Slabs, Terraces
- Swimming pools (tiled and untiled)
- Marine and zoo aquarium tanks
- Plaza decks and patios
- Water and waste water treatment tanks
- Balconies, parapet walls, planter boxes
- Underneath tile mortars in kitchens, bathrooms, etc.

www.shirazee.co.in

Mixing & Application:

- Take the 2/3rd content of the liquid component (The second component liquid of **MYK Aquafin 2C**) into a clean container and add **MYK Aquafin 2C** powder into it.
- Stir well with mechanical means @ 500-700 rpm until lump free homogeneous mix is obtained.
- The application of **MYK AQUAFIN-2C** is a simple brush application. Use soft bristle brush.

Consumption:

Typically 2-2.5 kg per Sqm subject to application areas.

Health & Safety

Use of hand gloves is necessary while mixing the product. In case of contact with skin or eyes, use plenty of water to wash and obtain medical help immediately.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.