

MYK AQUAFIN UM

2-component cement based flexible Waterproof Coating

Description:

MYK AQUAFIN-UM is an economic cementitious, polymer dispersion based highly flexible protective coating and waterproof barrier. This product is two-component and resistant to water, moisture and abrasion. Its liquid mixing component is solvent free.

MYK AQUAFIN -UM is a stand-alone product. It can be top or over-coated with flexible or rigid mortars, stuccos or coatings for uniform appearance. It bridges shrinkage cracks.

Pack Size: 33.33 Kg Pack

Advantages:

- Seamless and joint-less flexible waterproofing.
- Can be applied by brush, trowel or sprayed with suitable device
- Bonds to moist surfaces without prime coat.
- Diffusion opens. Act strongly aggressive towards concrete in accordance with DIN 4030.
- Highly crack-bridging.
- Solvent-free

Usage:

- Horizontal, Vertical or overhead applications
- Exterior (positive side) or interior (negative side) waterproofing of new or old below grade foundations.
- Balconies, plaza decks, in combination with a UV protection
- Underneath tile mortars (showers, sanitary rooms, kitchens, pools etc.
- Water, wastewater, sea water and marine aquarium tanks and other reinforced concrete structures.

www.shirazee.co.in

Mixing & Application:

- Take 1/3rd content of the liquid **MYK Aquafin UM** & pour into a clean container and add **MYK Aquafin UM** powder into it.
- Stir well with a mechanical means until lump free homogeneous mix is obtained.
- The application of **MYK AQUAFIN-UM** is a simple brush application. Use soft bristle brush.

Consumption:

1.5 to 2.5 kg subject to application areas.

Health & Safety

Use of hand gloves is necessary while mixing the product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.