

MYK BOND SBR 45R

Single Component SBR Based Bonding Agent

Description:

It is single component modified Styrene butadiene Rubber emulsion specially designed for use as a bonding agent. It is suitable as an admixture for obtaining waterproof concrete, plasters and mortars.

Pack Size: 125 ml, 1, 5, 10 & 20 Lit Pack

Advantages:

- ❖ White liquid, useful as waterproof coat.
- ❖ Useful as a bonding agent between old and new concrete surfaces.
- ❖ Excellent impermeability & durability in cement mortar.

Usage:

- ❖ Waterproofing & repairs of terrace
- ❖ Toilets
- ❖ Chajja
- ❖ Masonry wall
- ❖ Slopping RCC roofs etc
- ❖ Repairs to RCC slabs
- ❖ Waterproofing mortars/ concretes, in repair mortars/ concretes

Application:

Moisten the surface before doing the coating application.

Apply **MYK Bond SBR 45R** by brush application.

Note- Don't apply coating over loose and cracked plaster surface.

Dosage: 1 lit per 5 Kg of cement

Health & Safety

Adopt health & safety regulations in accordance with local laws. Care should be taken when handling **MYK Bond SBR 45R** as it may cause irritation due to its Cementitious nature (please refer to Material Safety Data Sheet for specifics). As typical on most job sites, applicators should wear protective clothing and gloves. Those handling and mixing **MYK Bond SBR 45R** should wear a face mask. Safety shoes and helmets must be worn by staff at all-times. **MYK SCHOMBURG** recommends the enforcement of stringent health and safety measures on all job sites.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.