

# MYK Coat ZP

## Epoxy Zinc Rich Primer

**Description:**

**MYK Coat ZP** is a two component anticorrosion primer for reinforced steel in concrete repairs. It actively resists corrosion within the confines of the repair location.

**Pack Size: 1 Kg Pack****Advantages:**

- Zinc rich system combats corrosion
- Permanent protection to the steel structure
- Excellent adhesion to steel
- Time Saving-touch dry after 35 to 40 Minutes
- Exhibits excellent bond strength in cementitious repair

**Usage:**

- Used as a primer on reinforced bars for anticorrosive system and in concrete repairs
- Also can be used on exterior surfaces as a coating of machinery, fertilizers tanks, and girders in industries.

**Mixing & Application:**

Stir the Hardener and Resin individually with drill mixer of proper size. Then add the entire content of the hardener into Resin container and stir the two components thoroughly using a low speed mixer for about 2 to 3 Minutes until a uniform color of the mixture is obtained.

Corroded steel shall be fully exposed and all loose scale and corrosion deposits shall be removed. Then apply **MYK Coat ZP** as soon as possible over the dry steel surface after completion of the preparation work by using brush.

**Consumption:**

6.5 m<sup>2</sup> per Kg @ 50 microns.

**Health & Safety**

Use of hand gloves is necessary while mixing the product. In case of contact with skin or eyes, use plenty of water to wash and obtain medical help immediately.

**Storage:** Store in cool dry place

**Shelf Life:** 12 months from date of manufacturing.