

MYK RUST CONVERTER

Description:

MYK Rust Converter is a rust treatment which stabilizes and converts adamantly adhering rust into an organo-complex compound, resulting in the formation of a tough non-porous and moisture repelling coating of good mechanical stability, abrasion resistance, bond strength and excellent anti-corrosive properties.

Packing: 1 lit pack

Advantages:

- Good mechanical stability
- Abrasion resistance
- Bond strength
- Excellent anti-corrosive properties

Application Areas:

- Oil refineries
- Chemical plant and petro chemical industries.
- Steel bridges steel work. Offshore and onshore equipments cranes.
- Marine equipments.
- Civil engineering, construction (steel reinforcement rods).
- Pipes & Steel structural

Application of MYK Rust Converter:

Apply rust converter with a brush or a roller. It is recommended that any loose rust be removed with a wire brush and the rusty steel surface washed with high pressure water to remove excess salt contamination. The rust converter will dry in 20 minutes however it takes 24 Hours to cure. Application of a second coating will ensure proper rust conversion.

Coverage:

It is applied in no. of coats which depend on the surface condition. No. coats to be applied until the desired results are obtained.

Health & Safety

Use of hand gloves is necessary while mixing the product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.