

MYK SANIFLEX

Elastomeric Waterproofing coating for wet areas

Description:

MYK Saniflex is an elastomeric, Single Component; liquid applied, seamless, breathable, synthetic rubber based waterproofing system , specially designed for wet areas.

Product: MYK Saniflex
Pack Size: 5 ,10 & 20 Kg

Product: MYK Aso- Unigrund GE
Pack Size: 10 & 25kg

Advantages:

- Easy to apply
- Seamless Waterproofing coating system
- Fast curing
- Excellent crack bridging
- Breathable

Usages:

- Bathroom
- Shower Areas
- Kitchen Areas

Mixing:

Open the **MYK Saniflex** container and using a suitable means mix the material for certain time. As the product is a single component mixing is easy and the product has good consistency.



Application:

a) MYK Aso Unigrund GE:

Apply one coat of **MYK Aso Unigrund GE** @ 0.2 kg/m² by brush on the prepared substrates (consumption depends on the surface condition). It should be allowed to dry (depends upon the surface condition and temperature) before coating with **MYK Saniflex**.

b) Application of MYK SANIFLEX:

The material should be evenly applied @ 1.2kg/m² in two coats for a DFT of 0.8mm after ensuring the primer is dried out. The first Coat should be applied horizontally and completely dry before the application of the second coat this will be purely based on the prevailing atmospheric conditions. More the ambient temperature lesser the time gap.

Health & Safety:

Use of hand gloves is necessary while mixing the product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.