

# MYK TOP 150

## Dry shake Non-metallic Floor Hardener

**Description:**

**MYK Top 150** is a single component ready to use, dry shake, monolithic, non metallic surface hardener.

**Pack Size:** 25 Kg Pack

**Advantages:**

- ❖ Good wear and abrasion resistant topping which are non-dusting
- ❖ Non-slip and anti skid even in areas where oil is spilled
- ❖ Monolithic bond with the base concrete
- ❖ Facilitates easy cleaning
- ❖ Long life and low maintenance
- ❖ It resists petrol, mineral oils etc
- ❖ Non-rusting and thus trouble free
- ❖ Increased strength and impact resistant

**Usage:**

- ❖ Industrial floors subject to Repair workshops heavy traffic Machine shops
- ❖ Loading areas/unloading areas
- ❖ Warehouse Floors
- ❖ Ramps and Trucking lanes
- ❖ Car parks and garage floors etc.

**Application:**

Application is carried out in two stages.

In 1st operation broadcast 50% of the material evenly on green stage of concrete. Then troweling is to be done to close pores & remove disc mark. The 2nd application is done immediately.

**Dosage:**

For Low traffic	– 2.5-3 kg/ m <sup>2</sup>
For Medium traffic	– 3.5-4.5 kg/ m <sup>2</sup>
For Heavy traffic	–4.5-6.57 kg/ m <sup>2</sup>

**Health & Safety**

Use of hand gloves is necessary while mixing the Product In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

**Storage:** Store in cool dry place

**Shelf Life:** 12 months from date of manufacturing.