

MYK TOP GUARD

Multipurpose Waterproof Coating

Description:

MYK TOP GUARD is a cementations, polymer dispersion based flexible protective coating and waterproof barrier. This product is two-component and resistant to water, moisture and abrasion. Its liquid mixing component is solvent free. **MYK TOP GUARD** is a stand-alone product. It can be top or over-coated with flexible or rigid mortars, stuccos or coatings for uniform appearance.

Packing: 8 & 40 Kg Pack

Advantages:

- ❖ Breathable
- ❖ flexible
- ❖ Self Curing

Usage:

- ❖ Balconies , Chajjas
- ❖ Toilet/ Bathrooms
- ❖ Roof & Terraces

Mixing:

MYK TOP GUARD comes in a pre-weighed composite bag of powder as Component A and Polymer liquid as Component B should be mixed in the ratio of **7.5 : 2.5** parts by weight and mixed in a clean container with the help of a slow speed drill (350-400rpm) fitted with a paddle arrangement. The material should be mixed for 3-4 minutes till we get a homogeneous mix which is free of any lumps. Never add liquid to powder, powder has to be added to the liquid slowly. Over mixing should be avoided.

Application of MYK TOP GUARD:

The mix material is to be applied on the prepared pre-wetted surface (SSD conditions) in 2 coats. The 1st coat should be applied horizontally and the second coat should be applied vertically after 4-6 hours @ 30° C of the first coat.

MYK TOP GUARD to be applied typically at 1.5-2.5 kg/m². (Subject to application requirement)

By brush:

The application of **MYK TOP GUARD** is a simple brush application. Use soft bristle brush.

Curing Of MYK TOP GUARD

MYK TOP GUARD is self curing under normal condition

The coated substrate/area can be exposed to:

- Rain ,vertical surface after approximately 4 hours @30°C temp.
- Rain ,horizontal surface after approximately 12 hours 30°C temp
- Foot traffic after approx. 2 day 30°C temp

Health & Safety

MYK TOP GUARD may cause irritation due to its Cementitious nature. As typical on most job sites, applicators should wear protective clothing, gloves, face mask, safety shoes and helmets.

Storage: Store in cool dry place

Shelf Life: 12 months from date of manufacturing.